

Index

A

Anodic bonding, 50, 62, 83

B

Batteries, 2–3, 7, 57, 280, 284, 383, 395

Bearing(s), 15–17, 29, 191–192, 197, 224,
226–230, 234, 240–249, 301, 365
journal, 14, 16, 29, 49, 58–61, 66–68,

78–79, 89–110, 113–123, 125,
127–129, 131–133, 138–139,
142–146, 152–153, 192–197,
200–234, 256–260, 264–265,
268–270, 272, 275–276, 292, 316,
328, 352

high-speed gas, 191–276

hydrodynamic, 16, 229

hydrostatic, 16, 28, 195–196, 222–223

rig, 58–60, 79, 82, 89–90, 97, 102–103,
107, 117, 119, 124–125, 267–269

ultra-short journal, 215

Blade uniformity, 60–61, 108–110, 112, 146

BOE (buffered oxide etcher), 62–64, 67,
70–71, 73–74, 80–81, 86–88,
92–93, 99–102, 106–107, 116–118,
121–122, 124, 126–127, 133, 135,
137, 139–140, 142–146

Bonded blades, 109, 113–114, 119, 121, 142,
152

Burst speed, 35, 328–329

C

Charging effect, 78

Chemical energy, 1–6

Combustion

catalytic, 22, 410, 413–414, 430–431, 434,
437, 451

gas phase, 22, 410, 420, 430

Controls, 13, 15, 18, 23–27, 35, 39, 41, 43,
45–46, 50, 58–59, 61, 64, 70–71,

77, 79, 88, 95, 98, 99, 105–106, 108,
112–113, 117–119, 122–123, 130,
132, 143, 152–153, 163, 170, 178,
181, 192, 233–234, 250, 264–265,
268–269, 279–280, 292, 294–295,
300, 316, 325, 333–334, 344,
349–352, 383–384, 388, 394–395,
397–399, 434–436, 438, 450

Creep, 12, 19–20, 35, 41–42, 82, 153, 310

Cube-square law, 11

Current density limits, 176, 331

D

DRIE (deep reactive ion etching), 14, 36–37,
57, 62–68, 70–80, 84–89, 91,
93, 95–119, 121–124, 130–137,
139–140, 142–146, 148, 152–153,
178, 181, 183, 192, 223, 271, 279,
415, 443, 445

E

Eddy currents, 160, 168–170, 180–181,
330–331, 335, 365–366, 370,
372–373, 378, 380, 392–393, 397,
399, 400

Efficiency, 2–6, 293, 301–302, 318, 346

combustor/combustion, 14, 21–22,
409–410, 414, 419, 421–423,
425–427, 432–434, 443

component, 28, 281

compressor, 280, 285, 306, 309, 313, 319

conversion, 5–6, 280–281, 284

cycle, 284, 290, 309, 311–312

3D, 287

engine, 43–44

isentropic, 287–288, 293, 311–313, 318

machine, 12, 365, 391

power, 58, 109, 153

electronics, 394

Efficiency (*cont.*)

- rig, 317, 319
- system, 6, 380–381, 391–394, 397–399
- turbine, 317–319

Electric breakdown, 327, 354

Electromagnetic rotor

- conductors, 338–339, 341–344, 347, 352–353, 355–356, 360, 362, 366, 400
- permanent magnets, 368, 372–373, 377–379, 382

Electromagnetic stator

- electrodes, 26, 332, 337–338, 340, 342, 348, 352–355, 357–359, 362
- insulators, 347, 352–354, 362
- windings, 160, 184, 363, 366–367, 369–370, 373–374, 377, 379–380, 385, 393, 399

Electromagnetic stress, 328

Electromagnetic torque, 326, 328, 352, 357–358

- Energy density, 2–3, 7, 158, 171, 173, 282–284, 326–327, 329, 371, 405
 - electric, 2, 326–328
 - magnetic, 158, 171, 173, 326–328

Engine

- design, 12–15, 28–30, 34, 43, 280, 282, 287–288, 296, 310, 313, 429–430
- pressure ratio, 12–13, 17, 28, 234, 282, 288, 292, 294–296, 302, 306, 312–313, 412

Environment, 3, 23

- ambient, 161, 179
- DRIE, 79, 98
- engine, 23
- operating, 3, 161
- plasma, 78, 135
- temperature, 22
- thermal, 25
- wafer-processing, 24

Etching, 10, 28, 39, 71, 123

- cycle, 72–73, 98–99, 108
- deep, 34, 37, 45
- nested mask, 87, 123, 144
- process, 15, 36, 43, 62, 70–71, 93, 178
- silicon, 45, 70, 98, 135, 178
- species, 72, 74–75, 79, 99–100
- technology, 29
- test, 63
- wet/dry, 70–71, 80, 178, 353–354

F

- Finite element analysis, 38
- Fluid dynamics, 195, 200, 204, 221, 226–227, 242, 279, 287, 422
- Free rotor method, 89, 95, 107, 114–115, 117, 142–143, 152–153
- Fusion bonding, 60–62, 64, 77, 79–82, 116, 120, 122–123, 128, 135–136, 141, 144–145, 150, 178–179, 196, 353, 415

G

- Gas turbine performance, 11, 311
- Generators
 - electric motors, 16, 25, 27, 30, 300, 325
 - magnetic motors, 27, 167
- Glass frit bonding, 50

H

- Heat engines, 1, 10–11, 16, 161
- High-speed gas bearings, 191–276
- High temperature strength, 39–42
- Hybrid structures, 43–49
- Hydrodynamic bearings, 16, 229
- Hydrostatic bearings, 16, 28, 195–196, 222–223

I

- Interconnects, 83, 165, 338–339, 351–352, 354–355, 358–359, 449

J

- Journal bearing, 14, 16, 29, 49, 58–61, 66–68, 78–79, 89–110, 113–123, 125, 127–129, 131–133, 138–139, 142–146, 152–153, 192–197, 200–234, 256–260, 264–265, 268–270, 272, 275–276, 292, 316, 328, 352

L

- Laplace's Equation, 337, 341, 343
- Lomakin effect, 197

M

- Machines
 - electric
 - design of, 26–27, 326
 - fabrication of, 291–292, 326, 334–335
 - induction, 26, 334–335, 337–363, 400
 - permanent electret, 334–335
 - variable-capacitance, 334
 - magnetic
 - design of, 26, 176
 - induction, 27, 180, 334, 352

- permanent-magnet, 183–186, 334–335, 363–400
 - variable reluctance, 158, 334
- Magnetic cores, 158, 160, 167, 169, 181, 363, 378
- Magnetic laminations, 183
- Magnetic saturation, 161, 167, 177–178, 326, 383
- Materials testing, 39, 53
- Mechanics, 8–13, 17–18, 31, 34, 52, 283, 287, 321
 - scaling, 12–13, 283
- MEMS, 1–8, 13–17, 19–20, 23, 25, 27–30, 33, 50–53, 57, 61–62, 64, 77, 158–161, 168, 171, 173, 176, 178, 191–194, 196–200, 213, 234–235, 256–257, 260, 262–263, 269–271, 274, 279–281, 284, 292, 296, 310, 314–321, 326–329, 332, 338, 343, 349, 351, 362
 - turbomachinery rotordynamics, 196–200
- Microcombustors/combustion, 20, 21, 22, 50, 51, 405–452
- Microengine, 11, 21, 33–35, 37, 39–40, 42–44, 47, 49–51, 53, 57–153, 161, 191, 193, 279–285, 287–292, 294–296, 299–300, 311–313, 325, 333–335, 378, 380, 382–383, 399, 405–406, 416, 425, 427–429, 436, 444–445, 451
- Microfabrication, 8–11, 13, 15, 17, 22, 29, 43–45, 157–162, 168–169, 171–172, 177, 184, 255, 257, 270, 279, 288, 292–294, 303–304, 309, 313–314, 326, 335, 361–362, 399, 445
- Micro gas
 - journal bearings, 205–210, 224–226, 229
 - seals, 195
 - thrust bearings, 192, 194, 226, 232–256, 264, 269–271, 274
 - turbine, 35, 59, 192, 412, 418
- Microheat engines, 1, 11, 16
- Motors
 - compressor, 30, 405
 - electric, 27, 30, 300, 325
 - magnetic, 27, 167
- N**
- Nozzle etch, 61, 83–84, 86–88
- P**
- Packaging, 19–20, 31, 33–53, 62, 83, 320, 411, 415, 443–449
- Permanent magnets (PM), 158, 173, 183–186, 334–336, 363–400
- Photolithography, 15, 62, 64–68, 80, 86–87, 99, 116, 137, 143, 279, 443, 444
- Photoresist, 64–65, 67, 70, 75, 77–78, 85, 87, 98–100, 107, 121, 135, 137, 142, 145–146, 152–153, 158, 163, 165, 168, 172–173, 181, 183, 291, 444–445
- Planarization, 47
- Portable power, 2–3, 400
- Power
 - density, 2–3, 6–7, 10, 16, 21, 26–27, 35, 181, 184, 187, 192, 281–282, 284, 292, 294–295, 326, 357–358, 362, 398–400, 411–414, 417, 419, 426, 428–429, 433, 442, 451
 - electronics, 325, 329–330, 332–333, 340, 349–352, 358–359, 362–363, 365, 378, 380, 383–390, 393–400
- PowerMEMS, 1–8, 192, 234–235, 256, 260, 284, 292, 321, 325–326, 328–333, 335, 337, 339–340, 349, 361
- Probabilistic design, 34, 38
- Profile control, 71, 79, 95, 99, 105–106, 108, 122
- R**
- Residence time, 10, 21, 407, 411–415, 417, 420–421, 426, 428–429, 434–435, 450
- Residual stress, 45–46, 50
- Rotor
 - dynamics, 15–17, 20, 28
 - releasing, 89–96, 131, 133
- S**
- Safety, 3
- Scaling, 9–13, 21, 25, 33–34, 38, 157–158, 170, 178, 205, 207–210, 217, 219, 226, 267, 271, 280, 282–285, 288–289, 295–297, 305, 321, 357, 379–380, 408
 - laws, 25, 157, 205, 207–210, 267–268, 271, 379–380
- Sealed cavity, 81, 91, 116, 120, 125, 127–130, 136, 139–141, 144, 178
- Self sustained engine (SSE), 57, 60–61, 79, 82–83, 90, 97, 107, 109, 117, 119, 121, 123–153
- Silicon, 12–14, 19–21, 36, 279
 - hybrid structures, 43–47
 - microfabricated, 35
 - rotor, 210, 314, 328, 349

Silicon (*cont.*)

- silicon carbide (SiC), 12, 19, 29, 43–49, 313
 - silicon dioxide, 179, 334, 338–339, 353–354, 448
 - silicon nitride, 12, 29, 63–64, 71, 106, 134
 - silicon oxide, 47, 62, 70–71, 78, 98–99, 134, 152
 - single crystal, 19, 35, 41–43, 279, 315, 443, 445
 - steel, 168, 328–329, 331
 - substrate, 179, 183, 353, 363, 365
 - surface, 36, 50, 52, 105, 320
 - turbine, 209, 274, 280
 - turbocharger, 315, 320
 - wafers, 14, 44–45, 179, 181, 279, 315, 320, 378, 415–420, 445
- Skin depth, 168–169, 181, 330–331, 370, 380
- Stiffness anisotropy, 223–233, 257, 267, 269, 272
- Strength, 11, 13, 311
 - bond, 37–38, 119, 130, 178–179
 - electric field, 10, 26, 327
 - fracture, 12, 19, 49
 - high-temperature, 39–42
 - mechanical, 38
 - room temperature, 36–39
 - usable, 10, 12, 19
- Stress compensation, 63, 81, 123–124, 126–128
- Structural design, 10, 19–20, 27, 33–34, 37–40, 42, 270
- Structures and materials, 15, 19–20

T

- Thermal limits, 328
- Thermal oxidation, 62–64, 71, 81, 86–88, 93, 116, 126, 133, 148
- Thermal shaft, 58, 60, 79, 82, 125, 131–132, 137–138
- Thermodynamics, 1, 9–13, 19, 28, 287, 308–309, 311, 313, 410, 415, 436, 450–451
- Tip clearance, 18, 84, 86–88, 305, 307, 309
- Turbine generator, 10, 28, 30, 295, 314, 325, 338, 352, 361, 363, 382, 399
 - electric, 9–10, 30, 295, 352, 361
 - magnetic, 325, 363
- Turbocharger, 9, 58–60, 84, 97, 111, 118, 125, 194, 204, 238, 240, 253–254, 256, 268, 281, 287, 314–321
- Two-side photo process, 69, 87, 122, 148

U

- Ultra-short journal bearings, 215

W

Wafer

- bonding, 34, 57, 60, 66, 80, 88, 113, 119–120, 124–125, 127, 129, 135, 141, 153, 178–179, 182–183, 268, 354–355, 358, 362, 415, 443, 445
 - mounting, 75
 - protection, 77
- Weibull statistics, 53
- Whirl instability, 192, 196, 198–200, 203, 208, 211–233, 269–272, 274