

Index

- Active power combiners and splitters, 2, 71, 75, 88, 92
- Actual or artificial transmission lines (TLs), 17–21, 24, 25, 28, 31, 33–35, 45–49, 51–53, 75–76, 79, 81, 92
- Analog correlator, 9, 10
- Analog-to-digital converter (ADC), 9–11, 46, 58
- Antenna-array, 72
- Attenuation constant, 60
- Autocorrelation function, 26, 27, 30
- Average transmit power, 12

- Bandpass matching network, 17
- Bandwidth
 - fractional bandwidth, 5, 7
 - signal bandwidth, 4, 12
 - wide bandwidth, 4, 5, 12
- Baseband, 8, 9, 10, 12, 13, 46, 57, 66, 72, 92
- Beamforming, 71–74, 79, 80, 83, 85, 88
 - vector, 71
- Beam pattern, 73, 74, 75
- Beam radiation angle, 74
- Beam-steering, 72, 79
- BER, 12–13
- Bias current, 19, 35, 47, 58
- Bipolar, 17, 18, 42, 55, 68
- Bit-interleaved coded modulation (BICM)
 - SNR, 10–11
- Bit rate (r_b), 12–13
- Blockers, 11, 59
- BlueTooth (BT), 5
 - coaxial cables, 5
- Boltzmann's constant, 27–28
 - absolute temperature, 27–28
- Broadband non-uniform amplifiers, 75
- Broadband resistive matching, 19

- Broadband variable delay, 71, 72–73, 74–76, 82
- Buffer, 82

- Cancellation of interferes, 72
- Cascaded LC circuits, 18
- CDMA, 11
- Channel capacity, 4, 91
- Channel thermal noise, 15, 25, 26, 27, 28, 30, 31
- CMOS, 1, 2, 8, 12, 13, 15, 17, 18, 20–24, 36, 42, 45, 51, 55, 57, 64, 75, 83, 87, 88, 91, 92
- Coarse-tuning, 79
- Co-existence, 1, 3
- Common-emitter, 18, 42
 - coplanar waveguides, 18
- Common-gate, 15, 17, 20, 21, 25, 33, 42
- Common-gate low-noise amplifier (CG-LNA), 17
- Common-mode, 52, 59, 66, 76, 85, 86
- Common-mode noise, 59
- Common-source, 15, 17, 18, 20, 21, 22, 26, 28, 42, 47, 57
- Complex variable, 31
- Composite cell, 2, 45, 47, 48, 49, 57, 58, 59, 64, 68, 92
- Composite LNTA/Mixer Cell, 47–48, 51, 53, 91
- Controllable delay, 72, 76, 78–79
- Convolution operation, 30
 - impulse function, 30
 - white noise process, 30
- Correlated and uncorrelated components, 27, 28
- Correlated channel thermal noise and gate-induced noise, 27
- Correlated gate-induced noise, 15–16
- Correlation coefficient, 28

- Correlator, 10, 11, 12
- Cross couple paths, 78
- Current equalization, 2, 57, 60–64, 66, 67, 69
- Current-equalized minimal-area distributed
 - direct conversion RF front-end DDC-RF, 2, 57–60, 62–68, 91–92
 - in phase/quadrature (IQ) phase and gain imbalance, 2, 57
- Current mirror, 24
- Current-mode LNA, 47–48
- Cutoff frequency, 18, 23, 33, 35, 38

- Damping factor, 23
- Data rate, 1–7, 13, 91
- Data transmission, 4
- Delay elements, 74, 75, 78, 82
- Differential-mode, 80
- Differential-pair transistors, 79, 85
- Digital projector, 7
- Digital signal processing (DSP), 12, 46
- Digital-to-analog converter (DAC), 79
- Direct conversion MB-OFDM UWB receiver, 11
- Dispersive channels, 10
- Distributed active power combiners, 71, 79–80, 92
- Distributed active power splitters, 73, 80–81, 82, 83, 88
- Distributed amplifiers DA, 18, 20, 24, 25, 26, 69, 92
- Distributed direct-conversion RF front-end (DDC-RF), 2, 57–68, 91–92
- Distributed integrated circuit, 1, 91
- Distributed low-noise amplifier (DLNA), 2, 15, 16, 20–21, 24–25, 27–29, 32, 34, 35–42, 91
- Distributed oscillators, 18
- Distributed RF front-end, 2, 45–47, 57–60, 91
- Diversity, 11, 71, 72, 73
- Drain-line termination, 31
- Driver, 9, 73, 82
- Dual conversion or zero/low IF, 11
- Duty cycles, 9

- EIRP equivalent isotropically radiated power, 12
- End-fire antenna array, 74
- Equalizer, 1
- ESD protection, 37

- Fading, 1, 8, 10, 15, 73, 85, 91, 92
- Fast Fourier transform (FFT), 11–12
- Federal communications commission (FCC), 1, 5, 7, 12

- Fiber optic, 3
 - TCP/IP, 3
 - wired LAN, 3
 - wireless local area networks (WLAN), 3, 5, 6, 9, 59
- Fine-tuning, 79
- Flat magnitude response, 35
- Flicker noise, 15, 25, 28, 31, 32, 33, 72
- Forward and backward propagation, 25, 27, 28
 - backward power gain, 25
 - forward power gain, 25, 32
 - MOS transistor, 16, 25, 27–31, 35, 36, 41
- Forward error correction (FEC), 10
- Friis equation, 12

- GaAs, 18, 71, 87
- Gain
 - linearity, 1, 12, 16, 36–37, 40, 47, 53, 58, 66, 69, 92
 - noise figure (NF), 1, 2, 12, 15, 16, 24, 26, 28, 33, 35, 38, 41, 72, 85
- Gain-bandwidth product (GBW), 18, 33, 34
 - millimeter-wave (MMW) broadband IC, 18
- Gain diversity, 71
- Gate aspect-ratio, 35
- Gate-line termination, 31–32
- Gate resistance, 20, 31, 60
- G_m -boosting technique, 17

- HDTV, 6, 7
 - player, 7
- High-precision time-of-arrival-based localization, 7
- HIPERLAN II, 10

- IEEE, 802.11a/b/g, 5
- IFFT, 11
- IF transceiver, 45
- Image rejection ratio (IRR), 60, 64
- Imaging sensors, 7
 - RF tags, 7
- Imaging technology, 7
- Impulse-radio (IR) UWB, 7
- In-band interferes, 59
- Inductor loss, 20, 49
- Industrial, scientific and medical (ISM), 5
- In-phase and quadrature (IQ) phase and gain imbalances, 2
- Input and output return losses, 16, 39, 40
- Input gate TL, 79, 81
- Input matching, 16, 17, 19, 48, 52, 53, 57, 61, 64, 79, 82, 91
- Input-referred 1dB compression-point ($P_{in,1dB}$), 40, 41

- Input-referred noise, 15, 21, 48
- Integrated circuit (IC), 1, 18, 75, 91
- Integrator, 10
- Inter-carrier interference (ICI), 8, 10, 15
- 3rd-intercept point (IP3), 36, 40
- Interference, 8, 9, 45, 73
- Interstage drain inductors, 83
- Interstage inductors, 20
- Intersymbol interference (ISI), 8, 10, 15
- IQ mismatches, 2
- Isotropic antenna, 12

- Light speed, 12
- Link budget, 12–13
- L-matched, 17
- Localization services, 7
- Local shunt-feedback, 16
- Long-channel device, 28
- Long distance localization, 4–5
- Low cost, 7, 12
- Low-field mobility μ_0 , 36
 - saturated drift velocity v_{sat} , 36
 - threshold voltage, 36
- Low-noise amplifiers (LNA), 1–2, 9–12, 15–21, 25, 32, 37–38, 41–42, 45–47, 58, 68
- Low-noise transconductance amplifier (LNTA), 2, 45–53, 57–60, 62, 64, 66, 91–92
- Lowpass filter, 12, 72
- Low power, 1, 3, 4, 7, 9, 12, 57, 69, 91, 92

- Main lobe, 74
 - radar beam, 74
- Matched load, 49
 - conversion gain's ripple, 50
- MA-UWB beamforming, 71, 79, 80, 83
- MA-UWB receiver, 79
- MA-UWB transmitter, 80, 87
- Maximally flat polynomial, 23
- MB-OFDM UWB, 8, 10–12, 13
- Medical imaging, 7
- Metropolitan area network MAN, 3
- Mixer
 - current commuting mixers, 59, 73
 - distributed mixers, 2, 18
 - downconversion mixers, 45, 46, 72
 - quadrature mixers, 11–12
- MMIC GaAs, 71
- Mobility degradation, 36
- Modulation, 8, 10, 12
- MOSFET's maximum frequency of oscillation, 33
- Motion detection radars, 7

- Multi-antenna (MA)-UWB
 - beamforming/diversity transceiver, 72–75
- Multi-antenna UWB (MA-UWB) transceivers, 2
- Multi-antenna UWB beamforming transceivers, 71–72
- Multi-band OFDM, 7, 8, 10, 11, 13
- Multi-band orthogonal frequency-division multiplexing (MB-OFDM), 7, 8, 10–12, 13
- Multi-carrier modulation, 10
- Multipath-dominated environment, 8
- Multipath environments, 8, 71
- Multipath fading, 1, 8, 15

- Narrowband, 5, 8, 9, 11, 16, 17, 36, 71
- Noise factor, 19–20
- Noise figure, 1–2, 12, 15–16, 24, 26, 28, 33, 35, 38, 72, 85
- Notch filter, 11, 36
- Notch filters, 11

- OFDM, *see* Multi-band OFDM
- On-chip TLs, 18
- On-wafer, 83, 85
- Out-of-band image frequencies, 45
- Out-of-band images, 11
- Out-of-band interferences, 45
- Output noise current, 26, 28, 30, 31
- Output noise power, 19, 28, 32

- Parallel resonant frequency, 22, 23
- Parasitic capacitance, 17, 18, 20, 21, 24, 31, 47, 57, 66
- Passband, 21, 49
- Passive impedance transformers, 81
 - on-chip, 82
- Path loss, 12–13
- Peak-to-average power-ratio (PAPR), 8, 11
- Personal digital assistants (PDAs), 3
- Phased array system, 71
- Phasor analysis, 76
- Point-to-point, high-speed data transmission, 4–5
- Poly gate resistances, 60
- Power amplifier (PA), 7, 8, 11, 71, 73
- Power combiners, 2, 71–72, 74, 75, 79–80, 88, 92
- Power consumption, 1, 7, 8, 18, 20, 44, 47, 49, 58, 73
- Power spectral density (PSD), 9, 26, 30
 - deterministic signals, 26, 27
- Power splitters, 71, 81–82

- Pre-select filter, 11, 45, 46, 58
- Programmable matching network, 47
 - complex frequency synthesizer, 47
- Propagation constant, 20, 24, 25, 28
- PSD, 24, 26, 27, 30, 31
- Pulse-based systems, 7
- Pulse generator, 8, 9, 10

- QPSK, 12–13
- Quadrature LO signals, 46

- Receiver, 2, 8–13, 15–16, 41, 45–47, 53, 57–64, 71–74, 79, 80, 91, 92
- Receiver sensitivity, 12, 74, 80
- Rectifier, 72
- Reflection coefficient Γ_L , 48, 59, 65
- Remote sensing, 7
- Resistive feedback amplifiers, 17
 - common-source LNAs, 17
- Resistive matching, 16, 19, 20
- RF detector, 72, 73
- RF front-end, 1, 2, 9, 12, 13, 15, 45–47, 50, 57, 91–92
- RF TL cut-off frequency, 60, 61, 63
 - gate-to-channel capacitance, 60
- RF TL termination, 48, 51–54, 59, 62, 64–68
- Ripple, 21, 49, 50

- Satellite area network SAN, 3
- Saturation, 35, 36, 66, 76, 85
- Series resonant frequency, 22
- Shannon, 4, 91
- Short-channel, 36
- Short-duration pulses, 8–9
- Shunt peaking inductors, 81–82
- SiGe BiCMOS, 37, 41, 42, 55, 71
- SiGe process, 16, 35
- Silicon, 1, 4, 15, 18, 71, 75, 91
 - bandwidth-enhanced cascode cell, 15
 - cascode cell, 15, 20, 21, 22, 24, 25, 31, 33, 35, 37
- Single phase, 46
- SNR signal-to-noise ratio, 4, 11, 12, 13, 74, 80
- Spiral inductors with Q-factors, 24
 - microstrip line, 24
- Spread spectrum, 7, 10, 91
- Spurious-free dynamic range (SFDR), 36
- Square spiral inductors, 37
- Stationary random process, 25, 27
- Statistical average, 26
- Steer, 71, 72, 75, 79
- Stochastic modeling, 25
- Sub-carriers, 11
- Switches, 13, 60, 78

- Symmetric DDC-RF, 62–64
- Synchronized, 10
- Systematic IQ phase and gain mismatches, 69

- Tail current transistors, 76
- Technology scaling, 8, 18
- Template pulse, 10
- Termination impedance, 19, 38
- Termination resistance, 16, 48, 59–60
- Thermal noise, 9, 12, 15, 19, 20, 25–28, 30, 31
- Thermal noise level, 12–13
- Time-domain noise current, 30
- Time duplex (TD) multiplexing, 12
- Time-invariant, 26
- TL tap-points, 78
- T-matched, 17
- Transceivers, 1, 2, 4, 7, 9, 12, 13, 71, 91
- Transconductance, 2, 21, 45, 48, 49, 57, 59, 60, 76, 92
- Transmission-line, 2
- Transmit antenna, 8, 71, 81, 85
- Transmit power, 4, 5, 12, 13, 71, 73
- Transmitters, 5, 8, 9, 11–13, 71–74, 80–81, 87, 92
- Triode, 53, 66, 76, 85
- Tuning range, 78, 79
- Two-tone test 3rd order input intercept point (IIP3), 53, 66
 - current equalization, 66

- Ultra-wideband (UWB), 1, 91
- Uncorrelated, 19, 27, 28, 80
- Uniform gate and drain artificial LC TLs, 20
- Unit cell, 75–78, 80–81
- Unlicensed frequency range, 5
- Un-matched RX, 48, 59
 - LO TL's loss, 49
 - phasor, 49, 76–77
 - voltage standing wave ratio “VSWR”, 48
- UWB distributed RF front-end(UWB-DRF), 45, 46–53, 55, 57, 58, 68, 91
- UWB transceivers, 1, 2, 9, 12, 13

- Varactors, 35, 37
- Variable-gain amplifier (VGA), 9–12, 46, 58
- Variable-gain DDC-RF, 58, 59
- Vector network analyzer (VNA), 37
- Velocity of light c , 74
- Velocity saturation, 36
- Viterbi decoder, 10–11
- Voice over IP (VoIP) headset, 6

- Wavelength λ , 74
- Weaver-type image-reject architecture, 45–46
 - automatic gain control (AGC), 11, 46, 58

- Weaver-type receiver, 60
- Wide area network (WAN), 3, 6
- Wideband, 49, 62, 81, 92
- Wideband bandpass filters (BPF), 17
- Wideband bandpass termination, 16
- Wideband matching, 15, 16, 45, 46, 47, 58, 75, 82, 85
 - bandwidth-enhancing inductors, 15, 41
 - distributed circuits, 15, 17, 18–20, 45, 57, 58, 71, 75, 91, 92
 - thermal noise of line terminations, 15–16
- Wideband RF front-ends, 1
- Wide-sense stationary (WSS), 26
- Wireless
 - networks, 3, 9
 - Wireless local area network (WLAN), 3
 - Wireless feedback, 73
 - Wireless personal area network WPAN, 3
 - Wireless sensing, 7
 - Wireless USB, 5, 7
 - Wireless WAN (WWAN), 3
 - WLAN blocker, 59
 - Worldwide interoperability for microwave access (WiMAX), 6
 - WWAN, 3–4
- Zero/low-IF dual conversion receiver, 45