

Bibliography

1. W. G. Cady. "Method of Maintaining Electric Currents of Constant Frequency", US patent 1,472,583, filed May 28, 1921, issued Oct. 30, 1923.
2. G. W. Pierce, "Piezoelectric Crystal Resonators and Crystal Oscillators Applied to the Precise Calibration of Wavemeters", Proc. American Academy of Arts and Sciences, vol. 59, October 1923, pp. 81-106.
3. G. W. Pierce, "Electrical System", US patent 2,133,642, filed Febr. 25, 1924, issued Oct. 18, 1938.
4. W. A. Marrison and J.W. Horton, "Precision Determination of Frequency". I.R.E. Proc. vol. 16, pp. 137154 Feb., 1928.
5. E. Vittoz, "The Electronic Watch and Low-Power Circuits", IEEE Solid-State Circuits Society News, Vol. 13, No. 3, Summer 2008, pp.7-23.
6. A. Hadjimiri and T. H. Lee, "A General Theory of Phase Noise in Electrical Oscillators", IEEE J. Solid-State Circuits, vol. 33, pp. 179-194, Febr. 1998. Corrections at page 928 of the same journal (June 1998).
7. V. Uzunoglu, *Semiconductor Network Analysis and Design*, McGraw Hill, 1964, p.245.
8. M.R. Spiegel, *Complex Variables*, Schaum Publishing Co, New York, 1964.
9. F.E. Terman, *Radio Engineering HandBook*, McGraw-Hill, 1943.
10. E. Momosaki, "A Brief Review of Progress in Quartz Tuning Fork Resonators", Proceedings of the 1997 IEEE International Frequency Control Symposium, 1997, pp. 552-565, 28-30 May 1997.
11. W. P. Mason, "A New Quartz Crystal Plate, Designated the GT, Which Produces a Very Constant Frequency Over a Wide Temperature Range", Proc. IRE, vol. 28, p. 220, May 1940.

12. J. Hermann, "A Novel Miniature ZT-Cut Resonator", Proc. of the 39th Annual Symposium on Frequency Control, 1085, pp. 375-380.
13. E. Vittoz, "Quartz Oscillators for Watches", invited paper, Proc. 10th International Congress of Chronometry, pp. 131-140, Geneva, 1979.
14. E. Vittoz, M. Degrauwe and S. Bitz, "High-Performance Crystal Oscillator Circuits: Theory and Applications", IEEE J. Solid-State Circuits, vol. SC-23, pp. 774-783, June 1988.
15. H. J. Reich, *Functional Circuits and Oscillators*, Boston technical Publishers, Cambridge MS, 1965.
16. D. B. Leeson, "A Simple Model of Feedback Oscillator Noise Spectrum", Proc. IEEE, Vol. 54, pp. 329-330, Febr. 1966.
17. C. Enz, F. Krummenacher and E. Vittoz, "An Analytical MOS Transistor Model Valid in All Regions of Operation and Dedicated to Low-Voltage and Low-Current Applications", Analog Integrated Circuits and Signal Processing, Vol.8, pp. 83-114, 1995.
18. C. Enz and E. Vittoz, *Charge-Based MOS Transistor Modeling*, John Wiley and Sons, Chichester, 2006.
19. H. Oguey and S. Cserveny, "MOS Modelling at Low Current Density", Summer Course on Process and Device Modelling. ESAT-Leuven, June 1983.
20. J. K. Clapp, "An inductive-Capacitive Oscillator of Unusual Frequency Stability", Proc. IRE, vol. 36, 1948, pp. 356-358.
21. E. Vittoz and J. Fellrath, "CMOS Analog Integrated Circuits Based on Weak Inversion Operation", IEEE J. Solid-State Circuits, vol. SC-12, pp. 224-231, June 1977.
22. D. A. Aebischer, H. J. Oguey and V. R. von Kaenel, "A 2.1MHz Crystal Oscillator Time Base With a Current Consumption under 500nA", IEEE J. Solid-State Circuits, vol. 32, pp. 999-1005, July 1997.
23. J. Santos and R. Meyer, "A One-Pin Oscillator for VLSI Circuits", IEEE J. Solid-State Circuits, vol. SC-19, pp. 228-236, April 1984.
24. J. Luescher, "Oscillator Circuit Including a Quartz Crystal Operating in Parallel Resonance", US patent 3,585,527, filed oct. 27, 1969, issued June 15, 1971.
25. D. Ruffieux, "A High-Stability, Ultra-Low-Power Differential Oscillator Circuit for Demanding Radio Applications", Proc. ESSCIRC'02, pp. 85-88, 2002.
26. M. P. Forrer, "Survey of Circuitry for Watches", Proc. IEEE, vol. 60, pp. 1047-1054, Sept. 1972.
27. J.A.T.M. van den Homberg, "A Universal 0.03-mm² One-Pin Crystal Oscillator in CMOS", IEEE J. Solid-State Circuits, vol. 34, pp. 956-961, July 1999.

Index

- amplitude
 - detector, 73
 - increase of, 62, 106
 - limitation, 27, 28, 58
 - of drain voltage, 94, 184
 - of gate voltage, 58, 61, 62, 65
 - of oscillation, 5, 61, 62, 65, 94, 146, 162
 - regulation, 73, 107, 122, 162
 - stability, 116, 117
 - regulator, 108
 - curve, 110, 121, 163
 - simplified, 117
 - stability, 5
- bias current, 61, 145
 - critical, 61, 64, 108, 161
 - start-up, 109
- bilinear function, 11, 43, 167
- capacitance
 - gate oxide, 37
 - load, 48
 - motional, 8
 - parallel, 8, 14
 - parasitic, 8
- capacitive
 - attenuator, 62
 - circuit impedance, 196
 - coupling, 22, 138
 - load, 123
 - transducer, 18
- channel length modulation, 39
 - voltage, 39
- channel noise excess factor, 40
- circuit impedance, 24, 43, 70, 165, 166, 191
 - for the fundamental, 24, 31, 55, 69
 - locus of, 24, 26, 56, 125
 - locus of, 43, 46, 52, 56, 134, 141, 158, 160, 162, 167, 170, 172, 187, 188, 191
 - real and imaginary parts, 167, 170, 172
- coupling
 - coefficient, 9, 18
 - electromechanical, 9
 - factor, 14, 18, 21
- critical
 - condition for oscillation, 27, 43
 - current, 108, 126, 161
 - minimum, 61, 64, 147, 194
 - supply voltage, 125, 126
 - transconductance, 44, 49, 59, 139, 143, 169, 170, 194
- current
 - bias, 65
 - specific, 37, 162
- cyclostationary noise, 33, 79, 81, 149, 151, 154, 157, 177, 179, 181
- design

- example, 89, 100, 117
 - process, 84
- differential pair, 137
- distortion
 - of drain current, 174
 - of gate voltage, 57
- drain current, 36
 - forward component of, 36
 - reverse component of, 36
- duality, 30
- dynamic behavior
 - of bias, 95, 97
 - of oscillation amplitude, 97, 100
- electromechanical
 - coupling, 9
 - transducing property, 16
- electrostatic transducer, 18
- energy
 - dissipation, 34
 - exchange of, 24, 34
 - kinetic, 15
 - mechanical, 7, 15, 68, 148
 - of oscillation, 33
 - potential, 15
 - thermal, 30
- equivalent circuit
 - of series resonance oscillator, 164
 - for small signal, 164
 - of parallel resonance oscillator, 140
 - for small signal, 140
 - of Pierce oscillator, 42
 - for small signal, 42
 - of quartz resonator, 8, 10
- figure of merit, 18–20, 22, 47
 - of dipole resonator, 14
 - of loaded dipole resonator, 139
 - of resonator, 10, 14
- frequency
 - adjustment, 54
 - parallel resonance, 11–13
 - pulling, 10
 - resonant, 8, 16, 138
 - series resonance, 11–13
 - stability, 69
- frequency pulling, 54, 139
 - at critical condition, 27, 44, 48, 142, 168, 171, 194
 - at stable oscillation, 26, 57
 - effect of losses on, 53
- fundamental component
 - of control voltage, 173, 174
 - of drain current, 59, 60, 63
 - of output current, 146, 147
 - of voltage, 24, 55
- impedance
 - motional, 8, 10
 - parallel, 11, 139
 - locus of, 11, 139
- impulse sensitivity function (ISF), 33, 34, 79, 81–83, 152, 153, 180, 182
- inversion
 - coefficient, 37
 - at bias current, 146
 - at critical current, 63, 174
 - strong, 37, 38
 - weak, 37, 38
- linear
 - analysis, 42, 55, 139, 144, 165, 172, 190, 193
 - approximation, 27
 - circuit, 27
 - noise, 31, 33, 150, 178
 - function, 103
 - impedance, 10
 - range of operation, 27
 - resistive element, 102
- load
 - capacitance, 48
 - resistance, 188
 - resistor, 165
- losses, 43, 163
 - effect of, 52, 54, 75, 143
 - on frequency pulling, 53
- lossless
 - capacitor, 46
 - circuit, 46, 51, 55, 84, 139

- mechanical
 - energy of oscillation, 15, 68, 148
 - power dissipation, 15, 68, 148
- MEM resonators, 18, 22
- mode
 - activity, 72
 - contour, 17
 - flexural, 16
 - fundamental, 10
 - of oscillation, 7
 - overtone, 10
 - thickness, 17
 - torsional, 17
 - unwanted, 71, 128
 - wanted, 10
- modulation index
 - of current, 173, 174, 180
 - of differential pair, 146
 - of gate voltage, 81
- MOS transistor
 - drain current, 36
 - EKV model, 36, 40, 55
 - intrinsic voltage gain, 39
 - saturation, 37
 - slope factor, 37
 - specific current, 37
 - threshold voltage, 37, 94
 - transfer function, 58
 - transfer parameter, 37
- motional
 - capacitance, 8
 - current, 9, 15
 - impedance, 8, 24, 30, 41, 68
 - locus of, 43, 141
 - inductance, 8
 - resistance, 8
- negative resistance, 41, 43, 44, 47, 52, 56, 137
 - current stable, 164
 - maximum, 47, 141, 142, 158, 160, 168, 191
 - voltage stable, 138
- noise
 - channel noise, 39
 - cyclostationary, 33, 79, 81, 149, 151, 154, 157, 177, 179, 181
 - excess factor, 31, 77, 78, 80, 83, 151, 152, 154, 195
 - flicker, 35, 81–83, 154, 157, 181, 183
 - model, 40
 - of bias current, 83
 - phase noise, 31, 35, 36, 77, 84, 149, 157, 177, 183
 - thermal, 35
 - white, 34, 35, 77–79, 81, 150, 154, 178, 180
- nonlinear
 - analysis, 55, 77, 144, 148, 172, 177
 - effects, 25, 55, 65, 69, 176, 189
 - simulation of, 56, 125, 176
 - example, 55
 - transfer function, 58, 65
- oscillation
 - amplitude, 24, 61, 62, 65, 146
 - critical condition for, 27, 43
 - energy, 15, 33
 - mode of, 8, 16
 - unwanted, 128
 - parasitic, 139, 166
 - signal extraction, 123, 185
 - stable, 25, 26, 31, 59
 - start-up of, 29
 - start-up of
 - time constant, 29, 47
- oscillator
 - applications of, 1
 - basics on, 4
 - comparison of, 194, 200
 - current-mode, 184
 - parallel resonance, 196
 - Pierce, 2, 41, 91, 93, 135, 195
 - CMOS inverter, 124, 131
 - grounded drain, 132, 135
 - grounded source, 93, 131
 - quartz, 1
 - series resonance, 197
 - single pin, 132, 190
 - symmetrical

- for parallel resonance, 137, 164
 - for series resonance, 164, 189
 - van den Homberg, 190, 193, 195
- parallel resonance oscillator, 137, 164, 196
- phase
 - noise, 31, 34–36, 77, 84, 149, 157, 177, 183
 - shift, 79–81, 150, 154, 180
 - stability, 5, 31, 43, 50, 138
- Pierce oscillator, 2, 41, 91, 93, 135, 195
 - CMOS inverter, 124, 131
 - current-controlled, 129, 131
 - simulation, 125
 - grounded drain, 132, 135
 - grounded source, 93, 131
- practical implementation
 - of parallel resonance oscillator, 157, 164
 - of Pierce oscillators, 93, 135
 - of series resonance oscillator, 183, 189
 - of van den Homberg oscillator, 193
- quality factor, 8, 24, 33, 44, 46, 53, 57, 70, 72, 77, 84, 89
- quartz
 - crystal, 15
 - production, 2
- quartz resonator, 7
 - cut
 - AT, 17
 - CT, 17
 - GT, 17
 - equivalent circuit, 8
 - resonant frequency of, 8
 - types of, 15
- resistor
 - elimination, 120
 - implementation, 102
 - load, 165
- resonance
 - parallel, 11, 138
 - series, 11
- resonant circuit
 - parallel, 30
 - series, 8, 30
- resonator
 - dipole, 14
 - mechanical, 7
 - MEM, 18, 21, 22
 - quartz, 7
- saturation
 - drain voltage, 94
 - of MOS transistor, 37
- series resonance oscillator, 164, 189, 197
- strong inversion, 37, 63, 80, 82, 94, 146, 152
 - strict, 66, 88, 94, 146
- thermodynamic voltage, 37
- transconductance
 - amplifier, 190
 - critical, 44, 49, 52, 59, 139, 143, 169, 170, 194
 - drain transconductance, 38
 - for the fundamental frequency, 59, 67, 146
 - gate transconductance, 38
 - in saturation, 39
 - limit for negative resistance, 167, 189
 - maximum, 49
 - optimum, 43, 46, 169
 - source transconductance, 38
- van den Homberg oscillator, 190, 193, 195
- weak inversion, 37, 60, 62, 64, 72, 79, 81, 86, 89, 94, 146, 151, 155